

Kjellberg
CUTTING



K 200

JUST CUTTING.

PLASMA CUTTING 0.036 - 2 3/8 INCHES



K 200

JUST CUTTING.

The K 200 offers exactly what plasma cutting is all about: optimum and reliable plasma cutting quality with easy operation at lowest cost.

The power source cuts with oxygen, air and nitrogen and provides a marking function. Integrated automatic gas control and direct torch connection simplify installation and maintenance of the system. Important data and parameters, as well as cutting data sets in the material thickness range from 0.036 - 2 3/8 inches can be intuitively accessed, selected and adjusted up to a maximum of 200 A.

Focus on what matters most

- ✓ Optimum and reliable cutting results
- ✓ Low investment and operating costs
- ✓ Simple installation, control and maintenance



Operating Modes of the Power Source

The plasma system can be operated in CNC mode via the serial interface (RS485).

For CNC guidance systems without a serial interface, the K 200 can be operated using the K-Desk app.

K-TORCH

MANUAL PLASMA CUTTING

Plasma Torches for best Cutting Results

- ✓ Machine torch K-Torch with direct connection and easily demountable shaft
- ✓ Quick-change torch K-Torch QC for easy change of consumables
- ✓ Hand torch K-Torch M for manual plasma cutting and gouging


K-Desk App

The K 200 can be controlled and monitored via smartphone. It can be connected via cable or optional by USB WLAN stick

The K-Desk app is available to download from both the Google Play Store and the Apple App Store.



K-DESK APP



- ✓ Intuitive menu-driven user interface
- ✓ All process and cutting parameters at a glance
- ✓ Individual selection and adjustment of cutting parameters

Technical Data		K 200
----------------	--	-------

Cutting current (100 % d.c. ¹)	60 - 200 A
Marking current (100 % d.c. ¹)	35 A

Cutting range		
Mild steel Maximum Piercing	O₂/Air 2 3/8 in 1 3/8 in	Air/Air 2 in 1 3/8 in
Stainless steel Maximum Piercing	N₂/ N₂ 1 5/8 in 1 in	Air/Air 2 in 1 1/4 in
Aluminum Maximum Piercing	N₂/ N₂ 1 5/8 in 3/4 in	Air/Air 2 in 1 1/4 in

Plasma gases	O ₂ , N ₂ , Air
Swirl gases	N ₂ , Air
Marking gas	Air

Dimensions (LxWxH)	43 x 27 x 49 in 1078 x 684 x 1231 mm
Mass	774 lbs/351 kg
Fuse, slow	80 A
Mains voltage ²	480 VAC 3 Phase, 60 Hz
Max. Connected load	52 kVA
Protection class	IP 21S

Extract Cutting speeds	
Mild steel 3/8 in O ₂ Cutting 130 A Air Cutting 130 A	114 in/min 106 in/min
Mild steel 3/4 in O ₂ Cutting 200 A Air Cutting 200 A	69 in/min 59 in/min
Stainless steel 3/8 in N ₂ Cutting 130 A Air Cutting 130 A	75 in/min 71 in/min
Stainless steel 3/4 in N ₂ Cutting 200 A Air Cutting 200 A	47 in/min 59 in/min
Aluminum 1/2 in N ₂ Cutting 130 A Air Cutting 130 A	71 in/min 71 in/min

¹ Ambient temperature 40 °C/104 °F

² Other voltages and frequencies on request

Contact

Kjellberg Cutting, Inc.

1504 Eagle Court Unit 6 | Lewisville | Texas 75057 | USA


Office: +1 469.770.9799 | sales@kjellbergcutting.com

www.kjellbergcutting.com

Copyright © 2024 Kjellberg Cutting, Inc.



09109124

Kjellberg, , Q, K, Smart Focus, HiFocus and PerCut are trademarks of Kjellberg Foundation and registered with the U.S. Patent and Trademark Office.

